



FRESNELED 100/300DMX

Model: ML FTV100/300



Via Pavoncelli, 75 – 70125 BARI (Italia) - Tel. +39.340.0714175
Rruga Sitki Çiço, 2 - 1017 TIRANA (Albania) - Tel. +355.69.2208328
Email : marellilighting@yahoo.it
Web : www.marellilighting.eu – www.ercolemarelligroup.eu

6. Technical Parameters:

Light Source:	100/200W/300W LED COB
Input Voltage(V):	90-250V ,50-60Hz
Lamp Luminous Efficiency(lm/w):	99%
Certification:	CE, EMC
Model Number:	ML FTV100/FTV200/FTV300
Usage:	Theatres, stage, robust housing
Control mode:	DMX 512, Auto run and Master/Slave,sound...
Setting and Addressing:	4-digit LED
DMX Data In/Out:	XLR 3Pin
Electronic Dimmer:	0-100% linear dimmer
Electronic Strobe:	1-30 flashes/second
Warranty:	2 year
Switch Power Supply	Built-in and auto switching
Power In:	Fixed
CRI (Ra>):	95
Working Lifetime(Hour):	60000
Center Beam illuminance:	1) 19°: 10,600Lux@2.5mtr
	2) 26°: 7,500Lux@2.5mtr
	3) 40°: 5,500Lux@2.5mtr
Drive Mode:	Constant Current
Emitting Color:	CW.
LED Colour temperature- Warm White	3200K
LED Colour temperature- Cold White	5600K
Cooling:	Entire casing as heat sink plus 1 noiseless fans

Flicker Free	Refresh Rate >2000 Hz
Lamp Luminous Flux(lm):	2000
IP Rating:	IP33
Shell Material	Silver
Key point:	Temperature-protected handly
Working Temperature	-40 °C- +60°C